



YachtCoatings
GRIP ANTISKID EXTRA
TECHINICAL DATA SHEET

Product description

Particle size selected powder in plastic material, odourless, to be used as an anti-slip additive in floor paints and/or boat blankets. It has excellent mechanical characteristics and resistance to the marine environment. The product can be mixed with any type of topcoat or varnish, mono or bi-component.

Product information

Finish	Powder		
Colour	Colourless		
Solids (by volume)	ASTM D2369		100%
Specific gravity	UNI EN ISO 2811-1		0,9 ± 0,2 g/cm ³
Packaging	0,15 kg		

Application and use

SURFACE PREPARATION

Add to the already catalyzed topcoat a percentage that may vary from 4% to 5% in volume, depending on the necessity. Mix carefully during and before the application.

APPLICATION PROCEDURE

Generally an adding of 4%-5% by volume on the product ready to use allows the application of two coats with an excellent functional and aesthetic effect. Mix frequently the additional paint: the granulate tends to float. Always apply 2 coats. With the 0.15 Kg packaging, it is possible to obtain from 3 to 5 litres of ready to use anti-sliding product.



YachtCoatings
GRIP ANTISKID EXTRA
TECHINICAL DATA SHEET

Storage

It is recommended to avoid exposure to air and extreme temperatures. To maximize the shelf life in the can, it is worth checking that the container is well closed during the storage and the temperature is between 10 °C and 35 °C. Avoid exposure to direct sunlight.

Safety rules

Comply with the provisions set by the local health and safety at work regulations. Avoid contact with the skin, for example. Operate in well-ventilated places and, if in closed areas, use vacuum cleaners, fans and air conveyors. During the application use appropriate protections (masks, gloves, glasses, etc.). Before using, read sections 7-8 of the SDS.

INSTRUCTIONS FOR THE DISPOSAL OF PRODUCTS AND PACKAGING

Empty packaging that contained products: Dispose of empty packaging according to the requirements of the waste disposal law, for example by taking them to the recycling center.

Packages containing the unused products: Dispose of the unused product in accordance with the law of disposal of such waste, for example by taking it to a recycling center, recycling of packaging is prohibited in this case. Do not empty into drains or watercourses. Product packaging must be kept indoor, and the temperature in the storage place must be between 10 °C and 35 °C. Do not expose to sunlight.

Notes

The values indicated in the present technical sheet can have slight variations from one batch to another. All data refer to the mixed product. The applied product must not come in contact with water, chemicals or subjected to mechanical stress before the curing is complete. The above information is the result of accurate laboratory tests and practical experience; however, since the product is predominantly used outside the manufacturer's control, Boero Bartolomeo S.p.A. can only guarantee its quality. The information contained in this sheet may be subject to revision by the Company. For clarification, updates or further information, it is recommended to contact Boero Bartolomeo S.p.A. directly. The present datasheet annuls and replaces every other precedent to this one.

Rev. January 2021

2